

IN THE CLAIMS

1. (Previously Amended) A method, comprising:

sending an optical signal from a first apparatus to a second apparatus based upon an

incident angle;

receiving a reflection having a reflected angle of said optical signal from said second

apparatus on a screen; and

adjusting a position of one of said apparatuses relative to the other apparatus by adjusting

said incident angle based upon said reflection.
2. (Original) The method of claim 1, wherein sending said optical signal from said first

apparatus to said second apparatus further comprises sending said optical signal from

an optical source affixed upon said first apparatus.
3. (Original) The method of claim 2, wherein sending said optical signal from said first

apparatus to said second apparatus further comprises directing an incident light from

said optical source based upon a predetermined incident angle.
4. (Original) The method of claim 3, wherein an optical signal from said first apparatus to

said second apparatus further comprises directing an incident light from said optical

source to a reflective material affixed upon said alignment object.
5. (Original) The method of claim 4, wherein adjusting said position of one of said

apparatuses relative to the other apparatus based upon said reflection further

comprises adjusting said incident angle.

6. (Cancelled).
7. (Cancelled).
8. (Original) The method of claim 1, wherein adjusting said position of one of said apparatuses relative to the other apparatus based upon said reflection further comprises adjusting the incident angle to change a location on the screen upon which said reflective light is received.
9. (Cancelled).
10. (Previously Amended) A system for positioning a first apparatus in relation to a second apparatus, comprising:

an optical source affixed to said first apparatus, said optical source for directing an incident light to said second apparatus; and

a light receiving unit to receive reflective light reflected from said second apparatus, said light receiving unit comprising a circuit to detect a position of said reflective light, said position of said reflective light being used to adjust the positioning of said first apparatus in relation to the second apparatus.
11. (Original) The system of claim 10, wherein said light receiving unit comprises a screen to receive said reflective light.
12. (Original) The system of claim 11, wherein said screen comprises a plurality of markings to provide a location on said screen upon which the reflective light is received.

13. (Original) The system of claim 12, wherein said light receiving unit comprises means for providing a signal that is indicative of said location on said screen upon which the reflective light is received.
14. – 17. (Cancelled).
18. (Original) The system of claim 10, wherein said first apparatus is a testing device.
19. (Original) The system of claim 18, wherein said testing device is at least one of a photometer and a radiometer.
20. (Original) The system of claim 10, wherein said second apparatus is a computer display device.
21. (Original) The system of claim 20, wherein said computer display device comprises a liquid crystal display (LCD) screen.
22. (Original) The system of claim 10, further comprising a reflective material affixed upon said second apparatus for providing said reflective light.
23. (Original) The system of claim 22, wherein said reflective material comprises a mirror.
24. (Cancelled).
25. (Cancelled).

26. (Currently Amended) An apparatus, comprising:
- means for sending an optical signal from a first apparatus to a second apparatus based upon an incident angle;
- means for receiving a reflection having a reflected angle of said optical signal from said second apparatus on a screen; and
- means for adjusting a position of one of said apparatuses relative to the other apparatus by adjusting said incident angle based upon said reflection.
27. (Previously Amended) An apparatus for positioning a first device in relation to a second device, comprising an optical source affixed upon said first device, said optical source comprising a screen, said optical source to provide an incident light at an incident angle directed towards said second device from which a reflected light is received upon said screen; said apparatus being adapted to adjust the relative positioning between said first and second devices based upon the position of said reflected light on the screen by adjusting said incident angle.
28. (Original) The apparatus of claim 27, wherein said screen comprises a plurality of markings to provide a location on said screen upon which said reflective light is received.
29. (Original) The apparatus of claim 28, wherein said apparatus further comprises means for providing a signal that is indicative of said location on said screen upon which the reflective light is received.

30. (Original) The apparatus of claim 27, wherein said reflective light is provided by a reflective material affixed upon said second device.
31. – 34. (Cancelled).
35. (Original) The apparatus of claim 27, wherein said first device is testing device.
36. (Original) The apparatus of claim 35, wherein said first device is at least one of a photometer and a radiometer.
37. (Original) The apparatus of claim 27, wherein said second device is a computer display device.
38. (Original) The apparatus of claim 27, wherein said second device is a television display device.
39. (Original) The apparatus of claim 37, wherein said computer display device comprises a liquid crystal display (LCD) screen.
40. (Original) A system for testing a computer display, comprising:
a testing unit for performing a test upon said computer display;
an optical source affixed to said testing unit, said optical source for directing an incident light to said computer display; and
a light receiving unit to receive reflective light reflected from said computer display, the location of said light receiving unit upon which said reflective light is received

being used to adjust the positioning of said testing unit in relation to the computer display.

41. (Original) The system of claim 40, wherein said light receiving unit comprises a screen to receive said reflective light.
42. (Original) The system of claim 41, wherein said screen comprises a plurality of markings to provide a location on said screen upon which the reflective light is received.
43. (Original) The system of claim 40, wherein said testing unit is at least one of a photometer and a radiometer.
44. (Original) The system of claim 40, wherein said computer display device comprises a liquid crystal display (LCD) screen.
45. (Original) The system of claim 40, further comprises a reflective material affixed upon said computer display for providing said reflective light.